

Bijlage 13b VRU

GVR

Systeem installatie

Type		Aantal	in PM	Ampere (mA)	Totaal A	Voltage	Antennes	Toelichting
MOI	TAB A Samsung 10.1 inch	1		2000	2	12V		
Navi	TOMTOM Truck 7250	1		1800	1,8	12V		
Navi-link	TOMTOM Link 510	1		150	0,15	12V		
Telefoon	Pei-Tel PTCarPhone 510	1		50	0,05	12V		
Handlamp	Streamlight Survivor Led 24V	6		400	2,4	12V	nvt	
4 gas meter	GMI PS200	1		400	0,4	12V	nvt	
Porto object	Motorola DP 4600e	6		425	2,55	12V	nvt	
Mobi C2000	Motorola MTM 5200	1		4000	4	12V	Combi GPS/GPRS	
Mobi Bedienscherm	type Smelt touch screen	1		0	0	12V	nvt	
Mobi I/O	Motorola PMWN4017C	1		0	0	12V	nvt	
Audioversterker	FP-PA20	1		1650	1,65	12V	nvt	
Porto C2000	Motorola MTP6550	2		400	0,8	12V	nvt	
Lader Motorola (met carkit en raamantenne)	Motorola PMLN6431A	1				12V	raamanttene	
Lader object porto	Wtech WTC 636	6		0	0	12V	nvt	
Koellade	Waeco. Type: Coolmatic CD 30 Art.Nr.: CD-030DC	1		3000	3	12-24V	nvt	
USB/MOI	USB-A 5V / 3A (minimaal per poort)	1		3000	3	12V		
USB/MOI	USB-C 9V / 3A (minimaal per poort) met Power Delivery	1		3000	3	12V		
Tbv toekomstige uitbreiding	+30	1		5000	5	12V		
Tbv toekomstige uitbreiding	+15	1		5000	5	12V		
					34,8	Ampere		