



LUX S

<i>voltage/current</i>	<i>max power</i>	<i>source</i>	<i>flux</i>	<i>optic</i>	<i>CRI</i>	<i>switching</i>	<i>mounting</i>	<i>CCT</i>	<i>finish</i>	<i>code</i>
IN 12V-350mA	4,2W	LED spot	366lm	17°	90	according to driver	surface	3000K	grey	BLUS180IN2IWAA
			372lm	46°						BLUS180IF2IWAA
			366lm	17°				4000K		BLUS180IN2INAA
			372lm	46°						BLUS180IF2INAA
			366lm	17°				3000K	black	BLUS180IN2IWAN
			372lm	46°						BLUS180IF2IWAN
			366lm	17°				4000K		BLUS180IN2INAN
			372lm	46°						BLUS180IF2INAN

note

cable 2m, peg BLUXSPEG not included, driver not included. Compatible control: 1-10V, DALI, DMX, Casambi, series connection

customizations

CCT 2700K



orientable spot

LUX S DRIVER

<i>version</i>	<i>voltage/current</i>	<i>max power</i>	<i>IP</i>	<i>switching</i>	<i>dimensions cm</i>	<i>code</i>
for 2 spots	350mA	12W	20	ON-OFF	9,8x3,3x2,2	WALIMLED08350
for 3 spots		17W			12,2x3,8x2,4	WALIMLED12350
		15W		dimnable 1-10V	10,3x6,7x2,1	WALI/DIMM/JOLLY
for 5 spots		25W			12,4x7,9x2,2	WALI/MAXI/JOLLY
note	for outdoor installation IP connection system not included					

ACCESSORIES

<i>version</i>	<i>finish</i>	<i>dimensions cm</i>	<i>code</i>
PEG for 1 spot	black	19x3x2	BLUXSPEG

